

Let us entertain you



Jamo D600

Imagine that you can experience the amazing sound quality you hear in the best cinemas in the world – but in the comfort of your own home. The D 600 is the newest Jamo sound system that is built and approved to the same quality standards as the best movie theaters in the world namely THX. This highly advanced Jamo system meets the THX Ultra 2 standard, but is a truly musical hi-fi speaker system.

Consisting of carefully designed elements equipped with advanced technology, these speakers are not only able to reproduce the same powerful and detailed sound that you would only expect in real life or the best cinemas, but they are also able to present a sound-stage that is as large in scale and physical appearance that it is hard to believe.

The D 600 system is elegant and discreet, fashioned in a modern and graphic style that is able to blend in easily with the interiors in most modern homes.

State-of-the-Art technology

Jamo has developed driver units especially for this high-end THX Ultra 2 system. Identical drivers used in both the LCR and surround-speakers result in perfect balance across the speakers, and a 15"/1600W subwoofer equipped with Motional Feedback, ensures a dynamic, detailed and precise reproduction of even the lowest spectrum. The subwoofer is equipped with a unique touch interface which gives the user a variety of settings.

Type System	D 600 SUB Active DSP based subwoofer, sealed enclosure, motional feedback Touch panel with backlight 380 / 15	Type System	D 600 LCR 3 Way closed
User interface	100m Vrms (line in only)	Woofer [mm/in]	2 x 165 / 6½
Woofer [mm/in]	Default, Personal, THX	Midrange [mm/in]	2 x 76 / 3
Rated power [W]	Yes, pass through for daisy chain.	Tweeter [mm/in]	25 / 1 DTT
Dynamic power [W]	On / Off	*Power long/shortterm [W]	200 / 300
Peak power [W]	115V/60Hz (6.3A) / 230V/50Hz (3.15A)	Sensitivity [dB/2,8V/1m]	89
Maximum SPL [dB]	Off / Auto / On	Frequency range [Hz]	80 - 20.000
Frequency range [Hz]	557 x 587 x 501 / 21.9 x 23.1 x 19.7	Cross-over frequency [Hz]	400 / 2.500
Variable cut off [Hz]	32 / 70.5	Impedance [Ohm]	4
Variable phase	Stone gray	Dimension HxWxD [mm / inch]	393 x 645 x 229/ 15.5 x 25.4 x 9 13 / 28.6
Level control [dB]		Weight [kg / lb]	
Boundary gain compensation		Type System	D 600 SUR 3 Way closed dipole
Line input	Yes, stereo pass through for daisy chain	Woofer [mm/in]	1 x 165 / 6½
LFE input	Yes, pass through for daisy chain	Midrange [mm/in]	2 x 76 / 3
Speaker level input	Yes	Tweeter [mm/in]	2 x 25 / 1 DTT
Sensitivity	100m Vrms (line in only)	*Power long/shortterm [W]	150 / 200
Sound modes	Default, Personal, THX	Sensitivity [dB/2,8V/1m]	87
12V trigger	Yes, pass through for daisy chain.	Frequency range [Hz]	80 - 20.000
Mains switch	On / Off	Cross-over frequency [Hz]	250 / 2.500
Voltage switch [fuse]	115V/60Hz (6.3A) / 230V/50Hz (3.15A)	Impedance [Ohm]	4
Auto enable switch	Off / Auto / On	Dimension HxWxD [mm / inch]	327 x 516 x 221/ 12.9 x 20.3 x 8.7 9 / 19.8
Dimension HxWxD [mm / inch]	557 x 587 x 501 / 21.9 x 23.1 x 19.7	Weight [kg / lb]	
Weight [kg / lb]	32 / 70.5		
Finishes	Stone gray		

THX and the THX logo are trademarks of THX Ltd. which may be registered in some jurisdictions. All rights reserved.

*) Long / Short term power, - according to IEC 268-5.